		_	_		_			_	Additions
		Width	Length	Weight			Design Speed	Safety Equipment	Requirement(s)
All-terrain vehicle	2	50 inches (maximum)	NS	1,500 lbs (maximum)	3 (minimum), nonhighway (6 inches in width minimum, wheel rim diameter 14 inches maximum)	v.	NS	NS.	
	SB73	50 inches (maximum)	NS	1,500 lbs (maximum)	3 ( minimum), nonhighway (would remove definition of	NS	NS	NS	
					"nonhighway")				
	AR	50 inches (maximum)	S	NS	3, 4, or 6; nonhighway	NS	NS		<1,000 cm <sup>3</sup> engine
	8	NS	NS	NS	3 or 4, low-pressure tires	straddle	SN	handlebars	3
	Æ	50 inches (maximum)	NS	1,200 lbs (maximum)	3 (minimum), nonhighway	NS	NS		operator only or
								taillight if operated in insufficient	passenger passenger
1974.16	⋝	NS	SS	1,200 lbs (maximum)	3-6, nonhighway	straddle	NS	ight if	<1,000 cm <sup>3</sup> engine displacement
	MO	50 inches (maximum)	S	600 (maximum)	3 (minimum), low pressure	straddle	SN	handlebar steering; brake system; muffler; spark arrester; if operated on street or highway, also headlamp and tall lamp lighted, "slow vehicle" emblem	
	웃	50 inches (maximum)	NS	NS	4 (minimum), nonhighway	NS	SN	THE STATE OF THE S	
Micro utility truck	22	48 inches (minimum)	160 inches	1,500 lbs (minimum)	NS	NS except cab required	40 mph minimum	cab	
mini-truck	웃	67 inches (maximum)	NS.	3,400 lbx (maximum)	4 (minimum)	NS except cab required	55 mph maximum	enclosed cab	<1,000 cm³ piston or rotor displacement
Work site utility vehicle	ক	48 inches (mlnimum)	135 inches (maximum)	800 lbs (minimum)	4 (minimum), low pressure	bench or bucket-type for 2 or more people	NS	steering wheel	
	SB73	48 Inches (minimum)	NS	800 lbs (minimum)	4 (minimum), nonhighway				
Recreational off-highway vehicle	ઢ	64 inches (maximum)	SS	2,000 lbs (maximum)	4 (minimum), nonhighway	nonstraddle	NS.	steering wheel	
	5873	>50 inches, 64 inches maximum	SN	2,000 lbs (maximum)	4 (minimum), nonhighway	NS	SN	NS.	
Recreational off-highway vehicle	Ą	75 inches (maximum)	NS	NS	4 or 6, nonhighway	NS	NS	muffler, spark arrester	<1,000 cm³ engine displacement
off-highway vehicle	8	NS	NS	NS	wheels or tracks	NS	SN	headlamp, talllamp, brakes, muffler, spark arrester	(includes ATVs)
off-road utility vehicle	⋝	type 1: <=50 inches type 2: <=65 inches type 3: <=65 inches	S	type 1: <=1,200 lbs type 2: <=2,000 lbs type 3: >2,000 lbs	4-8, nonhighway, or rubberized tracks	bucket or bench (not straddled)	NS	steering wheel or control levers	
utility-type vehicle (off-highway)	×.	74 Inches (maximum)	180 inches (maximum)	2,000 lbs (maximum)	4 (minimum), nonhighway	NS	SN	brake system, muffler system, spark arrester, lights if insufficient	1970-0-1
recreational off-highway vehicle	ç	65 inches (maximum)	NS	NS	4 (minimum), nonhighway	NS	SN	NS	
utility vehicle	è	NS	NS	NS	4 (minimum)	for 2 or more people	SN	steering wheel	
NS = not specified									